



**Powered Rooftop Maintenance Lifts**

# RV Rooftop Servicing



## Cost Effective Alternative to Engineered Overhead Harness Systems

500 lbs rated for 2 workers (with 4 to 1 safety factor)  
10' x 30" deck dimensions  
Leading rails padding (not shown)  
Low profile wheel assemblies for low clearance  
Adjustable lower perimeter railings  
Safety, set up instructions & labels  
Powder Coating available upon request.

Safety Compliant with OSHA regs  
7' height range  
54" width footprint (exceeds 3 to 1)  
Deck locks in at each corner  
Worm gear freefall protection  
Extension ladder worker access  
8" locking wheels

Deck hoist is adjusted by power drill to raise and lower deck and equipment

Railings are easily pushed out & retracted at height

Lower railing sections & corner wheels lift up to clear rooftop equipment



### Complete Packages:

*Effective Feb 20 17*

#### RV Maintenance:

includes 22" height extension frames for 12' 8" max height **\$12,795.00**

#### RV HighRise Package:

includes 34" height extension frames for 13' 8" max height **\$12,995.00**

Ships flat to save on freight. 2-3 hours assembly required



Remove perimeter railings for upper sidewall work



[sales@scissordeck.com](mailto:sales@scissordeck.com)

**604-230-2704**  
**1-877-730-2704**